Datasheet and description



Avide LED Downlight 38° Square 7W WW 3000K

Product code: ALDLS38WW-S-7W

Brand link: avidelighting.com/qr/ALDLS38WW-S-7W QR code:

ID: AB-190518 **Date of issue:** 2025-04-25

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen **Page:** 1/3

SPECIFICATIONS

EAN code: 5999097916088

Warranty: 3year(s)

Material: PC+PC

Working temperature: -20 -+40°c

Packaging: 1/b 100/c 1600/p

Certifications: CE

TECHNICAL DETAILS

Wattage: 7W

Voltage: 100-265V

Beam angle: 38°

Dimmability: No

Lumen output: 677lm

Color temperature: 3 000K

Lifetime: 25 000h

Energy class:

Type of LED: SMD2835
IP standard: IP20

BOX PICTURE



Datasheet and description



Avide LED Downlight 38° Square 7W WW 3000K

Product code: ALDLS38WW-S-7W

Brand link: avidelighting.com/qr/ALDLS38WW-S-7W **QR code:**

ID: AB-190518 **Date of issue:** 2025-04-25

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen **Page:** 2/3

PRODUCT SIZE

Diameter: 90mm
Height: 90mm
Cut out size: 75-85mm

CARDBOARD BOX

EAN: 5999097916088 Packaging: 1/b 100/c 1600/p

Dimensions: 125mm x 105mm x 52mm

Net weight: 66g Gross weight: 81g

CARTON

EAN: 5999097916095

Packaging: 1/b 100/c 1600/p

Dimensions: 640mm x 290mm x 440mm

Net weight: 6.6kg
Gross weight: 8.1kg

PALLET EXAMPLE

Height:

Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)

Cartons per pallet: 16carton/pallet

Cartons per row:

Net weight: 105.6kg Gross weight: 129.6kg

PRODUCT PICTURE



PRODUCT OUTLINE

Datasheet and description



Avide LED Downlight 38° Square 7W WW 3000K

Product code: ALDLS38WW-S-7W

Brand link: avidelighting.com/qr/ALDLS38WW-S-7W **QR code:**

ID: AB-190518 **Date of issue:** 2025-04-25

Company name: Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen **Page:** 3/3

PRODUCT DESCRIPTION

The Avide spot lamps can be recessed into suspended ceilings and can be fixed easily. The internal part of the frame can be tilted, thus the light of the installed lamp can be directed in the preferred angle for maximum light utilization. Its light is directed, emitting light at an angle of 38 ° in a focused way. Also ideal for lighting narrower spaces, including kitchen counters and cabinets with a mirror. Available both in round and square form.